

Nokian European

Nokian NTR 72 S

Sizes 385/65R22.5
385/55R22.5

Application All-season trailer tyre

- Also for steer axle use on main roads



Maximum load capacities per axle

Size	Pattern Design	LI/SS	Inflation Pressure	Single Load	Dual Load
385/65R22.5	NTR 72 S	158L	8,50 bar	8500 kg @120 km/h	-
		160K	9,00 bar	9000 kg @110 km/h	-
385/55R22.5	NTR 72 S	160K	9,00 bar	9000 kg @110 km/h	-
		158L	8,50 bar	8500 kg @120 km/h	-

Tyre dimensions

Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
385/65R22.5	NTR 72 S	15,0	11.75, 12.25	1068	386	492	3277	-
385/55R22.5	NTR 72 S	15,0	11.75, 12.25	1001	381	464	-	-

Compound Special compound for All-season use

Properties

- Wide zig-zag shaped grooves provide good grip
- Even tyre wear
- M+S marking
- Driving Safety Indicators (DSI)

Certificates

- E4-54R-0016904 (385/65R22.5)
- E4-54R-0020041 (385/55R22.5)
- E4-117R-010438-S (Noise homologation)

17.6.2009